## LIGHTING FIXTURE SCHEDULE

| TYPE | LAMP | Wattage | VOLTS | DESCRIPTION | MANUFACTURER 1 | MANUFACTURER 2 | MANUFACTURER 3 | TYPE COMMENTS |
|---|---|---|---|---|---|---|---|---|
| A1 | LED | 22 W | 277 V | 2'x4' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 3014 LUMENS, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 24CZ2-30-HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT4 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT24 SERIES AS AN APPROVED EQUAL. | |
| A2 | LED | 27 W | 277 V | 2'x4' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 3583 LUMENS, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 24CZ2-35-HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT4 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT24 SERIES AS AN APPROVED EQUAL. | |
| A3 | LED | 31 W | 277 V | 2'x4' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 4029 LUMENS, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 24CZ2-40-HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT4 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT24 SERIES AS AN APPROVED EQUAL. | |
| A4 | LED | 35 W | 277 V | 2'x4' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 4582 LUMENS, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 24CZ2-45-HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT4 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT24 SERIES AS AN APPROVED EQUAL. | |
| A4F | LED | 35 W | 277 V | 2'x4' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 4582 LUMENS, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS AND 2X4 DRYWALL FRAME KIT. | COOPER METALUX 24CZ2-45-HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK-DF-24-W | ACUITY BRANDS LITHONIA 2BLT4 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT24 SERIES AS AN APPROVED EQUAL. | |
| AA | LED | 123 W | 277 V | 48" DIA PENDANT FIXTURE, 15500 LUMENS, 125W, 3500K COLOR, 277V WITH MATTE WHITE ACRYLIE DIFFUSER WITH OUTSIDE AND INSIDE OVERLAY AND MULTIPLE VERTICAL CABLE MOUNTING. FIXTURE AND OVERLAY FINISHES TO BE AS SELECTED BY ARCHITECT. | CAMMAN LIGHTING P2440-48-LH-35K-CLV-2-WMB-XX-XX-ACM A3. | PRUDENTIAL LIGHTING O SERIES AS AN APPROVED EQUAL | OCL ARCHITECTURAL LIGHTING SOLO #SL1 SERIES AS AN APPROVED EQUAL. | FIXTURE TO BE PENDANT MOUNTED WITH BOTTOM AT +10'-0" AFF. |
| B1 | LED | 29 W | 277 V | 2'x4' GENERAL LED RECESSED FLAT PANEL, 3553 LUMENS, 29.3W, 3500K COLOR, 80 CRI. | COOPER METALUX LIGHTING 24FP3135C | ACUITY BRANDS LITHONIA CPANL SERIES AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA CFP SERIES AS AN APPROVED EQUAL. | |
| B2 | LED | 41 W | 277 V | 2'x4' GENERAL LED RECESSED FLAT PANEL, 4591 LUMENS, 41.4W, 3500K COLOR, 80 CRI. | COOPER METALUX LIGHTING 24FP4735C | ACUITY BRANDS LITHONIA CPANL SERIES AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA CFP SERIES AS AN APPROVED EQUAL. | |
| B2F | LED | 41 W | 277 V | 2'x4' GENERAL LED RECESSED FLAT PANEL, 4591 LUMENS, 41.4W, 3500K COLOR, 80 CRI WITH 2X4 DRYWALL FRAME KIT. | COOPER METALUX LIGHTING 24FP4735C-DF-24W-F | ACUITY BRANDS LITHONIA CPANL SERIES AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA CFP SERIES AS AN APPROVED EQUAL. | |
| B3 | LED | 60 W | 277 V | 2'x4' GENERAL LED RECESSED FLAT PANEL, 6091 LUMENS, 60.3W, 3500K COLOR, 80 CRI. | COOPER METALUX LIGHTING 24FP6435C | ACUITY BRANDS LITHONIA CPANL SERIES AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA CFP SERIES AS AN APPROVED EQUAL. | |
| BB | LED | 17.6 W | 277 V | 2'x2' LED TROFFER WITH MICROPRISMATIC CENTER LENS, 17.6W, 2072 LUMENS, 2500K COLOR, 80 CRI WITH SOFT WHITE ACRYLIC CENTER SHIELD AND EARTHQUAKE CLIPS. | ACUITY BRANDS MARK ARCHITECTURAL LIGHTING WHSPR-2X2-80CRI-35K-NODIM-MVOLT-SWC-LATC | FOCAL POINT FEQ22 SERIES AN APPROVED EQUAL. | FINELITE HPR SERIES AS AN APPROVED EQUAL. | |
| C1 | LED | 21 W | 277 V | 2'x2' GENERAL LED RECESSED FLAT PANEL, 2205 LUMENS, 20.7W, 3500K COLOR, 80 CRI. | COOPER METALUX LIGHTING 22FP2135C | ACUITY BRANDS LITHONIA CPANL SERIES AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA CFP SERIES AS AN APPROVED EQUAL. | |
| C2 | LED | 29 W | 277 V | 2'x2' GENERAL LED RECESSED FLAT PANEL, 3307 LUMENS, 29.2W, 3500K COLOR, 80 CRI. | COOPER METALUX LIGHTING 22FP3235C | ACUITY BRANDS LITHONIA CPANL SERIES AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA CFP SERIES AS AN APPROVED EQUAL. | |
| C2F | LED | 29 W | 277 V | 2'x2' GENERAL LED RECESSED FLAT PANEL, 3307 LUMENS, 29.2W, 3500K COLOR, 80 CRI WITH 2X2 DRYWALL FRAME KIT. | COOPER METALUX LIGHTING 22FP3235C-DF-22W-U | ACUITY BRANDS LITHONIA CPANL SERIES AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA CFP SERIES AS AN APPROVED EQUAL. | |
| D1 | LED | 15 W | 277 V | 2'x2' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 2030 LUMENS, 15W, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 22CZ2-20HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT2 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT22 SERIES AS AN APPROVED EQUAL. | |
| D1F | LED | 22 W | 277 V | 2'x2' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 3014 LUMENS, 22.4W, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 22CZ2-20HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT2 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT22 SERIES AS AN APPROVED EQUAL. | |
| D2 | LED | 22 W | 277 V | 2'x2' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 2474 LUMENS, 22.4W, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 22CZ2-24HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT2 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT22 SERIES AS AN APPROVED EQUAL. | |
| D3 | LED | 24 W | 277 V | 2'x2' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 3426 LUMENS, 24.3W, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 22CZ2-34HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT2 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT22 SERIES AS AN APPROVED EQUAL. | |
| D4 | LED | 29 W | 277 V | 2'x2' LED SPECIFICATION GRADE BASKET STYLE TROFFER, 3997 LUMENS, 28.5W, 3500K COLOR, 80 CRI, 120-277V DRIVER, RIBBED FROSTED ACRYLIC LENS WITH EARTHQUAKE CLIPS. | COOPER METALUX 22CZ2-34HE-UNV-L835-CD-1-CZ2-EQCLIP-U-PK | ACUITY BRANDS LITHONIA 2BLT2 SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA LCAT22 SERIES AS AN APPROVED EQUAL. | |
| F1 | LED | 10 W | 277 V | 2' LED SURFACE STRIPLIGHT WITH FLAT DIFFUSE LENS,1500 LUMENS, 80CRI, 4000K COLOR, GENERAL DISTRIBUTION, DIMMING DRIVER, PIR INTEGRAL OCCUPANCY SENSOR AND FINISH BY ARCHITECT. | ACUITY BRANDS LITHONIA CLX-L24-1500LM-SEF-FDL-MVOLT-EZ1-40K-80CRI-MSD7-XX | COOPER METALUX 2SNLED SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA MPS2 SERIES AS AN APPROVED EQUAL. | WALL MOUNT, COORDINATE WITH MECHANICAL AND PLUMBING EQUIPMENT IN CHASE |
| F1A | LED | 10 W | 277 V | 2' LED SURFACE STRIPLIGHT WITH FLAT DIFFUSE LENS, 1500 LUMENS, 80CRI, 4000K COLOR, GENERAL DISTRIBUTION, DIMMING DRIVER, FINISH BY ARCHITECT. | ACUITY BRANDS LITHONIA CLX-L24-1500LM-SEF-FDL-MVOLT-EZ1-40K-80CRI-XX | COOPER METALUX 2SNLED SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA MPS2 SERIES AS AN APPROVED EQUAL. | PENDANT MOUNT AT +9'-0" AFF, COORDINATE WITH MECHANICAL AND ELECTRICAL EQUIPMENT |
| F2 | LED | 19 W | 277 V | 4' LED SURFACE STRIPLIGHT WITH FLAT DIFFUSE LENS, 3000 LUMENS, 80CRI, 4000K COLOR, GENERAL DISTRIBUTION, DIMMING DRIVER, PIR INTEGRAL OCCUPANCY SENSOR AND FINISH BY ARCHITECT. | ACUITY BRANDS LITHONIA CLX-L48-3000LM-SEF-FDL-MVOLT-EZ1-35K-80CRI-MSD7-XX | COOPER METALUX 4SNLED SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA MPS4 SERIES AS AN APPROVED EQUAL. | WALL MOUNT, COORDINATE WITH MECHANICAL AND PLUMBING EQUIPMENT IN CHASE |
| F3 | LED | 19 W | 277 V | 4' LED PENDANT STRIPLIGHT WITH FLAT DIFFUSE LENS, 3000 LUMENS, 80CRI, 3500K COLOR, GENERAL DISTRIBUTION, DIMMING DRIVER AND FINISH BY ARCHITECT. | ACUITY BRANDS LITHONIA CLX-L48-3000LM-HEF-FDL-MVOLT-EZ1-35K-80CRI-XX | COOPER METALUX 4SNLED SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA MPS4 SERIES AS AN APPROVED EQUAL. | PENDANT MOUNT AT +9'-0" AFF, COORDINATE WITH MECHANICAL AND ELECTRICAL EQUIPMENT FOR FINAL LOCATION |
| F4 | LED | 25 W | 277 V | 4' LED SURFACE STRIPLIGHT WITH FLAT DIFFUSE LENS, 4000 LUMENS, 80CRI, 3500K COLOR, GENERAL DISTRIBUTION, DIMMING DRIVER AND FINISH BY ARCHITECT. | ACUITY BRANDS LITHONIA CLX-L48-4000LM-HEF-FDL-MVOLT-EZ1-35K-80CRI-XX | COOPER METALUX 4SNLED SERIES AS AN APPROVED EQUAL. | HUBBELL LIGHTING COLUMBIA MPS4 SERIES AS AN APPROVED EQUAL. | WALL MOUNT, COORDINATE WITH MECHANICAL AND PLUMBING EQUIPMENT IN CHASE |
| G1 | LED | 8.2 W | 277 V | 6" ROUND ARCHITECTURAL DOWNLIGHT, 750 LUMENS, 3500K COLOR, SEMI-SPECULAR FINISH, CLEAR REFLECTOR, WHITE FLANGE AND WET LOCATION RATED | ACUITY BRANDS LITHONIA LDN6-35/07-L06-AR-LSSS-MVOLT-GZ10-TRW | COOPER HALO HC6 SERIES AN APPROVED EQUAL. | HUBBELL PRESCOLITE LBP6 SERIES AN APPROVED EQUAL. | |
| G2 | LED | 9.6 W | 277 V | 6" ROUND ARCHITECTURAL DOWNLIGHT, 1000 LUMENS, 3500K COLOR, SEMI-SPECULAR FINISH, CLEAR REFLECTOR, WHITE FLANGE AND WET LOCATION RATED | ACUITY BRANDS LITHONIA LDN6-35/10-L06-AR-LSSS-MVOLT-GZ10-TRW | COOPER HALO HC6 SERIES AN APPROVED EQUAL. | HUBBELL PRESCOLITE LBP6 SERIES AN APPROVED EQUAL. | |
| J1 | LED | 33 W | 277 V | 8" x 54", ROUGH SERVICE FIXTURE, PENDANT CHAIN MOUNT, 4000 LUMENS, 3500K COLOR, CLEAR POLYCARBONATE LENS, MEDIUM DISTRIBUTION, UL LISTED FOR WET LOCATION, STAINLESS STEEL TAMPER RESISTANT LATCHES, IP65/66 RATED. | COOPER METALUX 4VT3 SERIES AS AN APPROVED EQUAL. | ACUITY BRANDS LITHONIA VAP-4000LM-PSU-MD-MVOLT-GZ10-35K-80CRI-STSL | HUBBELL LIGHTING COLUMBIA LXEM4 SERIES AS AN APPROVED EQUAL. | FIXTURE TO BE MOUNTED AT +12'-0" AFF U.O.N. |
| L1A | LED | 46 W | 277 V | 2' X 2', GRID LAY-IN IMPACT AND VANDAL RESISTANT FIXTURE, 46 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS CONCEALED PIANO HINGE, LED NIGHT LIGHT, 14 GAUGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. | KENALL RMCD2-TG-0/0-45L35K-DCC-1-DV-2/J-1-DLN | L.C. DOANE COMPANY CRC-LED SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 57R22 SERIES AS AN APPROVED EQUAL. | |
| L1B | LED | 46 W | 277 V | 2' X 2', GRID LAY-IN IMPACT AND VANDAL RESISTANT FIXTURE, WET LOCATION RATED, 46 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS CONCEALED PIANO HINGE, 14 GUAGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. | KENALL RMCD2-TG-0/0-45L40K-DCC-1-DV-2/J-1-WL | L.C. DOANE COMPANY CRC-LED SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 57R22 SERIES AS AN APPROVED EQUAL. | |
| L2A | LED | 46 W | 277 V | 2' X 4', GRID LAY-IN IMPACT AND VANDAL RESISTANT FIXTURE, 46 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS CONCEALED PIANO HINGE, 14 GUAGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. | KENALL RMCD4-TG-0/0-45L35K-DCC-1-DV-2/J-1 | L.C. DOANE COMPANY CRC-LED SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 57R24 SERIES AS AN APPROVED EQUAL. | |
| L3A | LED | 74 W | 277 V | 2' X 2', GRID LAY-IN IMPACT AND VANDAL RESISTANT FIXTURE, 74 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS CONCEALED PIANO HINGE, LED NIGHT LIGHT, 14 GAUGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. | KENALL RMCD2-TG-0/0-67L35K-DCC-1-DV-2/J-1-DLN | L.C. DOANE COMPANY CRC-LED SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 57R22 SERIES AS AN APPROVED EQUAL. | |
| L4A | LED | 25 W | 277 V | 1' X 2', GRID LAYIN IMPACT AND VANDAL RESISTANT FIXTURE, 25 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.375" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS CONCEALED PIANO HINGE, 14 GUAGE STAINLESS STEEL HOUSING WITH WHITE POWDER COAT FINISH. | NEWSTAR LIGHTING 37M12-H-H-L2-35-1-3/B-UN-WL | KENALL LIGHTING AS AN APPROVED EQUAL. | L.C. DOANE COMPANY AS AN APPROVED EQUAL. | FIXTURE TO MOUNT FLUSH IN BULKHEAD OUTSIDE OF SHOWER. ADJUST LOCATION AS NEEDED TO AVOID SANITARY PIPING ABOVE. |
| M1 | LED | 50 W | 277 V | 12" X 48", SURFACE CEILING MOUNT, IMPACT AND VANDAL RESISTANT FIXTURE, 50 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COAT FINISH, 14 GUAGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COATE FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. UL LISTED FOR DAMP LOCATION. | KENALL SDSA-4-0/0-45L35K-DDC-DV-2/J-1 | L.C. DOANE COMPANY TUST SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING WARN4 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED ON BOTTOM OF PRECAST WHERE INDICATED ON PLANS. |
| M1A | LED | 50 W | 277 V | 12" X 48", SURFACE CEILING MOUNT, IMPACT AND VANDAL RESISTANT FIXTURE, 50 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COAT FINISH, 14 GUAGE STAINLESS STEEL HOUSING WITH WHITE POWDER COATE FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. UL LISTED FOR WET LOCATION | KENALL SDSA-4-3/3-45L35K-DDC-DV-2/J-1-WL | L.C. DOANE COMPANY TUST SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING WARN4 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED ON BOTTOM OF PRECAST WHERE INDICATED ON PLANS. |
| M1B | LED | 50 W | 277 V | 12" X 48", IMPACT AND VANDAL RESISTANT FIXTURE, 50 WATT, 5000K, SURFACE CEILING MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COAT FINISH, 14 GUAGE STAINLESS STEEL HOUSING WITH WHITE POWDER COATE FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. UL LISTED FOR WET LOCATION WITH LED NIGHT LIGHT. | KENALL SDSA-4-3/3-1-45L50K-DDC-1-DV-2/J-1-WL-DLN | L.C. DOANE COMPANY TUST SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING WARN4 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED ON BOTTOM OF PRECAST WHERE INDICATED ON PLANS. |
| M1N | LED | 50 W | 277 V | 12" X 48", SURFACE CEILING MOUNT, IMPACT AND VANDAL RESISTANT FIXTURE, 50 WATT, 3500K, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COAT FINISH, 14 GUAGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COATE FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. UL LISTED FOR DAMP LOCATION, LED NIGHT LIGHT. | KENALL SDSA-4-0/0-45L35K-DDC-DV-2/J-1-DLN | L.C. DOANE COMPANY TUST SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING WARN4 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED ON BOTTOM OF PRECAST WHERE INDICATED ON PLANS. |
| M2 | LED | 73 W | 277 V | 12" X 48", IMPACT AND VANDAL RESISTANT FIXTURE, 73 WATT, 4000K, SURFACE CEILING MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COAT FINISH, 14 GUAGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COATE FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. UL LISTED FOR DAMP LOCATION. | KENALL SDSA-4-0/0-1-67L40K-DDC-1-DV-2/J-1 | L.C. DOANE COMPANY TUST SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING WARN4 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED ON BOTTOM OF PRECAST WHERE INDICATED ON PLANS. |
| M2N | LED | 73 W | 277 V | 12" X 48", IMPACT AND VANDAL RESISTANT FIXTURE, 73 WATT, 4000K, SURFACE CEILING MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COAT FINISH, 14 GUAGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COATE FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. UL LISTED FOR DAMP LOCATION, LED NIGHT LIGHT. | KENALL SDSA-4-0/0-1-67L40K-DDC-1-DV-2/J-1-DLN | L.C. DOANE COMPANY TUST SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING WARN4 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED ON BOTTOM OF PRECAST WHERE INDICATED ON PLANS. |
| N1 | LED | 50 W | 277 V | 8" X 48", IMPACT AND VANDAL RESISTANT FIXTURE, 50 WATT, 3500K, SURFACE CORNER WALL MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COATED FINISH, 14 GAUGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. | KENALL CD4-0/0-1-45L35K-DCC-1-DV-2/J-1-RGT | L.C. DOANE COMPANY AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 554 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED BELOW PRECAST IN CORNER WHERE INDICATED ON PLANS. |
| N1N | LED | 25 W | 277 V | 8" X 48", IMPACT AND VANDAL RESISTANT FIXTURE, 50 WATT, 3500K, SURFACE CORNER WALL MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COATED FINISH, 14 GAUGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. PROVIDE LED NIGHT LIGHT | KENALL CD4-0/0-45L40K-DCC-DV-2/J-1-RGT-DLN | L.C. DOANE COMPANY AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 554 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED BELOW PRECAST IN CORNER WHERE INDICATED ON PLANS. |
| N2 | LED | 28 W | 277 V | 8" X 24", IMPACT AND VANDAL RESISTANT FIXTURE, 25 WATT, 3500K, SURFACE CORNER WALL MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COATED FINISH, 14 GAUGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. | KENALL CD2-0/0-1-25L35K-DCC-1-DV-2/J-1-RGT | L.C. DOANE COMPANY AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 554 SERIES AS APPROVED EQUAL | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED BELOW PRECAST IN CORNER WHERE INDICATED ON PLANS. |
| N2N | LED | 28 W | 277 V | 8" X 24", IMPACT AND VANDAL RESISTANT FIXTURE, 25 WATT, 3500K, SURFACE CORNER WALL MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COATED FINISH, 14 GAUGE COLD ROLLED STEEL HOUSING WITH WHITE POWDER COAT FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSORY. REMOVABLE GEAR TRAY. | KENALL CD2-0/0-1-25L35K-DCC-1-DV-2/J-1-RGT-DLN | L.C. DOANE COMPANY AS AN APPROVED EQUAL. | NEWSTAR LIGHTING 554 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED BELOW PRECAST IN CORNER WHERE INDICATED ON PLANS. |
| P1A | LED | 28 W | 277 V | 12" X 24", SURFACE CEILING MOUNT, IMPACT AND VANDAL RESISTANT FIXTURE, 28 WATT, 3500K, SURFACE CEILING MOUNT, 0.125" PRISMATIC POLYCARBONATE INNER LENS, 0.500" CLEAR POLYCARBONATE OUTER LENS, CONTINUOUS HINGED LENS FRAME WITH WHITE POWDER COAT FINISH, 14 GUAGE STAINLESS STEEL HOUSING WITH WHITE POWDER COATE FINISH. TAMPER RESISTANT TORX SCREWS WITH SCREWDRIVER ACCESSOR. REMOVABLE GEAR TRAY, UL LISTED FOR WET LOCATION WITH LED NIGHT LIGHT. | KENALL SDSA-2-3/3-1-25L35K-DCC-1-DV-2/J-1-DLN-WL | L.C. DOANE COMPANY TUST SERIES AS AN APPROVED EQUAL. | NEWSTAR LIGHTING WARN2 SERIES AN APPROVED EQUAL. | ALL JOINTS IN FIXTURE AND BETWEEN FIXTURE AND MOUNTING SURFACE SHALL BE FILLED COMPLETELY. FIXTURE TO BE SURFACE MOUNTED ON BOTTOM OF PRECAST WHERE INDICATED ON PLANS. |
| SA | LED | 129 W | 277 V | SINGLE ARM POLE MOUNT, 19745 LUMENS, 151 W, 4000K COLOR, 70 CRI, 970 mA CURRENT DRIVE, TYPE II DISTRIBUTION, 4 LED LIGHT SQUARES, AND HOUSING SIDE SHIELD WITH FINISH AS SELECTED BY ARCHITECT.<br>POLE: 30' SQUARE STRAIGHT ALUMINUM POLE, 6" SHAFT SIZE, 0.25" THICK WITH FULL BASE COVER AND FINISH AS SELECTED BY ARCHITECT TO MATCH FIXTURE. | COPPER LUMARK PRV-PA2-B-740-U-T2R-XX-HSS<br>POLE: COOPER SSA-6-X-30-W-XX | ACUITY BRANDS LITHONIA RSX2 SERIES AS AN APPROVED EQUAL.<br>ACUITY BRANDS LITHONIA SSA SERIES POLE AS AN APPROVED EQUAL. | HUBBELL LIGHTING ASL1 SERIES AS AN APPROVED EQUAL.<br>HAPCO RTA SERIES POLE AS AN APPROVED EQUAL. | POLE MOUNT AT +30'-0" AFG |
| SB | LED | 129 W | 277 V | SINGLE ARM POLE MOUNT, 19745 LUMENS, 151 W, 4000K COLOR, 70 CRI, 970 mA CURRENT DRIVE, TYPE II DISTRIBUTION, 4 LED LIGHT SQUARES WITH FINISH AS SELECTED BY ARCHITECT.<br>POLE: 30' SQUARE STRAIGHT ALUMINUM POLE, 6" SHAFT SIZE, 0.25" THICK WITH FULL BASE COVER AND FINISH AS SELECTED BY ARCHITECT TO MATCH FIXTURE. | COPPER LUMARK PRV-PA2-B-740-U-T2R-XX<br>POLE: COOPER SSA-6-X-30-W-XX | ACUITY BRANDS LITHONIA RSX2 SERIES AS AN APPROVED EQUAL.<br>ACUITY BRANDS LITHONIA SSA SERIES POLE AS AN APPROVED EQUAL. | HUBBELL LIGHTING ASL1 SERIES AS AN APPROVED EQUAL.<br>HAPCO RTA SERIES POLE AS AN APPROVED EQUAL. | POLE MOUNT AT +30'-0" AFG |
| SC | LED | 129 W | 277 V | SINGLE ARM POLE MOUNT, 19431 LUMENS, 151 W, 4000K COLOR, 70 CRI, 970 mA CURRENT DRIVE, TYPE IV FORWARD THROW DISTRIBUTION, 4 LED LIGHT SQUARES WITH FINISH AS SELECTED BY ARCHITECT.<br>POLE: 30' SQUARE STRAIGHT ALUMINUM POLE, 6" SHAFT SIZE, 0.25" THICK WITH FULL BASE COVER AND FINISH AS SELECTED BY ARCHITECT TO MATCH FIXTURE. | COPPER LUMARK PRV-PA2-B-740-U-T4W-XX-HSS<br>POLE: COOPER SSA-6-X-30-W-XX | ACUITY BRANDS LITHONIA RSX2 SERIES AS AN APPROVED EQUAL.<br>ACUITY BRANDS LITHONIA SSA SERIES POLE AS AN APPROVED EQUAL. | HUBBELL LIGHTING ASL1 SERIES AS AN APPROVED EQUAL.<br>HAPCO RTA SERIES POLE AS AN APPROVED EQUAL. | POLE MOUNT AT +30'-0" AFG |
| SD | LED | 129 W | 277 V | SINGLE ARM POLE MOUNT, 20332 LUMENS, 151 W, 4000K COLOR, 70 CRI, 970 mA CURRENT